

## MXS 3.8

### CTEK BATTERY CHARGER 12V, 0,8/3,8A

- perfect charging and constant maintenance
- electronic safe
- splash water and dust proof (IP 65)
- **7-step charging program with LED indicators**
- **5 years warranty**

#### Technical Specifications:

Rated voltage:	220-240 V AC; 50-60 Hz
Charging voltage:	14,4 V or 14,7 V; nominal 12 V
Back current drain:	<1,3mA (approximately 1 Ah/month, when charger is connected to battery, but not to mains)
Charging current:	<b>0,8 or optional 3,8 A</b>
Charger type:	7-step, fully automatic IUoUp with pulse charging (re-animation of discharged batteries)
Dimensions :	168 x 65 x 38 mm (LxWxH)
Insulation class:	IP 65
Weight:	0,6 kg
Battery types:	open, maintenance-free AGM, GEL and lead-calcium
Charging time:	15 hours (for a 60 Ah battery)
Charging steps:	<b>1 - Desulphation</b> <b>2 - Soft start</b> <b>3 - Bulk</b> <b>4 - Absorption</b> <b>5 - Analyse</b> <b>6 - Float</b> <b>7 - Pulse</b>

Connecting cables with battery clamps and with eyelets (for permanent installation) plus one storage bag are included.

The MXS 3.8 charger replaces the proven model MXS 3.6.  
The new charger provides an improved 7-step charging program.